Revision: 15.11.2022

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 3 (replaces version 2)

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Product name PreTone Steel

· Article number: 10612-700015-000

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Paint

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: LOBA GmbH & Co. KG Leonberger Straße 56 - 62 D-71254 Ditzingen

Tel.: +49 (0)7156/357-0

· Informing department: service@loba.de

· 1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), Trisodium bis-[3-hydroxy-4-[(2-hydroxy-1-naphthyl)-azo]-7-nitronaphthalene-1-sulphonato(3-)]-chromate(3-). May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- **Description:** Mixture of the substances listed below with harmless additions.

(Contd. on page 2)

Revision: 15.11.2022

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.11.2022 Version number 3 (replaces version 2)

#### Product name PreTone Steel

(Contd. of page 1) · Dangerous components: CAS: 57693-14-8 Trisodium bis-[3-hydroxy-4-[(2-hydroxy-1-naphthyl)-≥0.1-<0.25% EINECS: 260-906-9 azo]-7-nitronaphthalene-1-sulphonato(3-)]-Reg.nr.: 01-2119969289-17 chromate(3-) Aquatic Chronic 2, H411; 🕩 Eye Irrit. 2, H319; Skin Sens. 1, H317 CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-≥0.00025-<0.0015% EC number: 911-418-6 one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-Index number: 613-167-00-5 one [EC no. 220-239-6] (3:1) Reg.nr.: 01-2120764691-48 Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; 🚱 Skin Corr. 1C, H314; Eye Dam. 1, H318; ♠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100);  $\langle 1 \rangle$  Skin Sens. 1A, H317 Specific concentration limits: Skin Corr. 1C; H314: C ≥0.6 % Skin Irrit. 2; H315:  $0.06 \% \le C < 0.6 \%$ Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319:  $0.06 \% \le C < 0.6 \%$ Skin Sens. 1A; H317: C ≥ 0.0015 %

## SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · After inhalation Supply fresh air; consult doctor in case of symptoms.
- · After skin contact The product is not skin irritating.
- · After eye contact Rinse opened eye for several minutes under running water.
- · After swallowing In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

Additional information For the wording of the listed hazard phrases refer to section 16.

## **SECTION 5:** Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents Use fire fighting measures that suit the environment.
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

## SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

GE

Printing date 15.11.2022

*Version number 3 (replaces version 2)* 

Product name PreTone Steel

(Contd. of page 2)

Revision: 15.11.2022

### SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions necessary if used correctly.
- Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- ·Storage
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Storage class 12
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures Wash hands during breaks and at the end of the work.
- · Breathing equipment: Not required.
- · Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material:  $\geq 0.4$  mm

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

0 °C

*Value for the permeation: Level*  $\leq 6$ 

· Eye/face protection Safety glasses recommended during refilling.

### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

Physical state
Colour:
Smell:
Odour threshold:
Fluid
Dark grey
Recognisable
Not determined.

· Melting point/freezing point:

· Boiling point or initial boiling point and boiling

range 100 °C

(Contd. on page 4)

Version number 3 (replaces version 2) Printing date 15.11.2022 Revision: 15.11.2022

Product name PreTone Steel

(Contd. of page 3)

· Flammability	Not applicable.
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	Not applicable
Decomposition temperature:	Not determined.
· pH at 20 °C	7.5
Viscosity:	
Kinematic viscosity	Not determined.
dynamic:	Not determined.
Solubility	
· Water:	Not miscible or difficult to mix
Partition coefficient n-octanol/water (log value)	-1.37997
Steam pressure at 0 °C:	6.11 hPa
Density and/or relative density	
Density at 20 °C	$1.003 \ g/cm^3$
Relative density	Not determined.
Vapour density	Not determined.
· 9.2 Other information	
Appearance:	
· Form:	Fluid
· Important information on protection of health an	ed Control of the Con
environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
Explosive properties:	Product is not explosive.
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard classe	<u> </u>
· Fynlosiyas	Void

· Information with regard to physical hazard cl	asses
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flamma	ble
gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability

· Desensitised explosives

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Void

- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 5)

Printing date 15.11.2022

Version number 3 (replaces version 2)

Product name PreTone Steel

(Contd. of page 4)

Revision: 15.11.2022

· 10.6 Hazardous decomposition products: No dangerous decomposition products known

## **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity
- · LD/LC50 values that are relevant for classification:

55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Oral	LD50	457 mg/kg (rat)
Dermal	LD50	660 mg/kg (rat)
		0.33 mg/l (rat)
	LC50/96 h	0.188 mg/L (fish)

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

EC50/48 h	0.1 mg/L (daphnia)
EC50/72 h	0.1 mg/L (daphnia) 0.027 mg/L (Algae) 0.0012 mg/L (Algae) 0.004 mg/L (daphnia) 0.098 mg/L (fish)
NOEC	0.0012 mg/L (Algae)
	0.004 mg/L (daphnia)
	0.098 mg/L (fish)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.

(Contd. on page 6)

Printing date 15.11.2022

Version number 3 (replaces version 2)

#### Product name PreTone Steel

(Contd. of page 5)

Revision: 15.11.2022

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number		
ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according	g to IMO	
instruments	Not applicable.	
UN "Model Regulation":	Void	

## **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Alteration in the context will be marked with a cross (\*).

· Relevant phrases

H301 Toxic if swallowed.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eve damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing data specification sheet: Productmanagement.

(Contd. on page 7)

Printing date 15.11.2022

Version number 3 (replaces version 2)

#### Product name PreTone Steel

(Contd. of page 6)

Revision: 15.11.2022

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

\* Data compared to the previous version altered.

GB